

Natural Uranium Content in Ground Waters of Mohali and Fatehgarh Districts of North Punjab (India) for the Assessment of Excess Cancer Risk

Hardev Singh Virk¹

¹ SGGS World University

Received: 9 December 2015 Accepted: 4 January 2016 Published: 15 January 2016

Abstract

LED Fluorimeter has been used to measure the uranium content of the ground water samples of Mohali and Fatehgarh districts of North Punjab (India). 33 locations have been selected for the present investigation. The aim of this study is to investigate the uranium content of the ground water in Northern districts of Punjab for sake of comparison with its occurrence in Southern districts of Punjab; and to assess the radiological and chemical risk due to the uranium present through ingestion. The uranium concentration of the water samples of the studied villages varies from 0.63 to 57.82 $\mu\text{g l}^{-1}$ with an average value of 16.93 $\mu\text{g l}^{-1}$. The uranium content of all the samples in groundwater lies within the safe limit of 60 $\mu\text{g l}^{-1}$ (ppb) of uranium proposed by AERB, India.

Index terms—

1 Introduction

The presence of natural Uranium in rocks, soils, plants and even in sea water makes its transportation easy in the environment. The rocks of the particular area are the prime source of the uranium to the environment. The solubility of the uranium in water in hexavalent (U^{6+}) form and to precipitate as a discrete mineral in tetravalent (U^{4+}) form, the uranium got deposited in the earth's surface provided to the favorable geological or environmental conditions. Surface water and especially ground water plays a vital role in the migration and redistribution of the nuclides in the earth's crust. Uranium present in water is transferred to plants and hence it enters the food chain and it becomes a source of health hazard to the humans. The World Health Organization recommended a reference level of the permissible limit of Uranium in drinking water 30 $\mu\text{g l}^{-1}$ (WHO) [1]. The accumulation of the uranium inside the human body results in its chemical and radioactive effects for two important target organs being the kidneys and lungs [2-4]. Uranium and radium have the bone seeking properties hence the kidneys, liver and the bones become the principle sites of deposition. The toxicity of uranium depends upon many factors like the route of exposure, particle solubility, contact time, and route of elimination [5]. Drinking water is the major source of the uranium to the human body. Drinking water contributes about 85% and food contributes about 15% of ingested uranium [6]. An exposure of about 0.1 mg/kg of body weight of soluble natural uranium results in transient chemical damage to the kidneys [7]. Uranium is a radioactive heavy metal, it decays into many other radioactive metals or gases which can further become a health hazard [8]. Though Uranium is a weak radioactive metal, if uranium content of the drinking water is high it may be hazardous. Due to high concentration of uranium in water and its extent of getting ingested into human body, the assessment of risk of health hazards are important. Uranium estimation of water systems of the Punjab State and the neighboring areas has been reported by some workers [9-15]. The objective of present investigations is health risk assessment due to natural uranium in drinking water in Mohali and Fatehgarh districts of North Punjab.

2 II.

The Study Area a) Location S.A.S Nagar (Mohali) district is located in the eastern part of the Punjab state and lies between North latitudes of $30^{\circ}21'00''$ and $30^{\circ}56'00''$ and East longitudes of $76^{\circ}30'00''$ and $76^{\circ}55'00''$ covering a geographic ambience of 1189 sq.km. The district is bounded by Patiala and Fatehgarh Sahib districts in the south-west, Ropar district in the northwest, Chandigarh and Panchkula in the east and Ambala district of Haryana state in the south. Fatehgarh Sahib district is located in southeastern part of Punjab state and lies between $300^{\circ}25'00''$ to $300^{\circ}45'45''$ north latitude & $760^{\circ}04'30''$ to $760^{\circ}35'00''$ east longitude covering an area 1147 sq. km.

3 b) Geomorphology and Soil types

The area can be broadly grouped into two depending upon its geomorphic features as alluvial fan and alluvial plains. Alluvial fans are deposited by hill torrents with a wavy plain rather than a steep slope. Adjacent to the alluvial fan are the alluvial plains which forms a part of large Indo-Gangetic Quaternary basin comprises of thick sand and silty sand layers interbedded with silt and clay beds. The alluvial plains are of vital economic value as it supports the dense population of the district. The soils are mainly developed on alluvium under the dominant influence of climate followed by topography and time. The major soil type of the district is weakly solonized tropical arid brown soils. In Fatehgarh Sahib district, the soils are loamy sand at the surface and calcareous sandy loam in subsurface layers. Sand constitutes 80% in the soil profile, silt constitutes 11%, and clay 9% in the soils.

4 III.

5 Methodology a) Sampling

Sample collection was done in both the districts in a contiguous area starting from Mohali tehsil, then entering Fatehgarh tehsil and winding up in Mohali in a circular loop. Before collecting the sample, we run the hand-pump or motor for few minutes and then collected the samples in the pre-processed bottles after rinsing twice with the water to be collected. Samples were filtered with 0.45 micron filter paper. The samples were analyzed within a week.

6 b) LED Fluorimeter

Quantalase has developed Fluorimeters which use banks of pulsed LEDs to excite fluorescence in sample under study. The wavelength, pulse duration and peak power of the LED output can be set to match the excitation requirements of the sample. The fluorescence is detected by a pulsed photomultiplier. Suitable filters after the LEDs and before the photomultiplier tube prevent LED light from reaching the photomultiplier tube directly. The filters can be broadband coloured glass filters or multilayer narrow band filters. The instrument is controlled by a microcontroller which pulses the LEDs and photomultiplier tube. The microcontroller also controls the ADC which convert the fluorescence signal from photomultiplier to digital form for further processing. A single board computer averages the photomultiplier output over 2000 pulses and carries out any calculations necessary. A touch screen display permits the operator to set necessary parameters and also display the fluorescence measurement.

7 c) Calibration of Fluorimeter

Standard solution of Uranium is used to calibrate LED Fluorimeter. The instrument was calibrated in the range of 1-100 ppb using a stock solution of standard which was prepared by dissolving 1.78g uranyl acetate dehydrate ($\text{CH}_3\text{COO})_2\text{UO}_2 \cdot 2\text{H}_2\text{O}$) in 1L of Millipore elix-3 water containing 1ml of HNO_3 . The blank sample containing the same amount of fluorescing reagent was also measured for the uranium concentration. 5% phosphoric acid in ultra-pure water was used as fluorescence reagent. All reagents used for experimental work were of analytical grade.

8 d) Preparation of FLUREN (Buffer Solution)

Weigh 5gms of Sodium Pyrophosphate powder and add it to a flask/plastic bottle. Add 100ml. of double distilled water and shake well to dissolve the Sodium Pyrophosphate powder. Add Ortho-phosphoric acid drop by drop while monitoring the pH of solution until a pH of 7 is reached. This is the desired buffer solution, also called FLUREN.

Adding buffer solution to a uranium sample increases the fluorescence yield by orders of magnitude. It is recommended that 1 part of buffer solution be added to 10 parts of uranium sample solution and this mixture be used for measurements.

9 e) Analytical Procedure

A water sample of quantity 6ml is used to find its uranium content. The water sample is taken in the clean and dry quartz cuvette made up of ultrapure fused silica. The instrument was calibrated with the standard uranium solution of known activity. The water sample of quantity 6 ml is mixed with 10% of the buffer solution. Buffer

solution is made from sodium pyrophosphate and orthophosphoric acid of pH 7. Buffer solution is used to have the same fluorescence yield of all the uranium complexes present in the water.

10 f) Theoretical Formulation

Ingestion of the uranium through drinking water results in both radiological risk (carcinogenic) and chemical risk (non-carcinogenic). The methodology used for the assessment of the radiological and chemical risk due to uranium concentrations in the water samples is described below:

11 g) Radiological risk assessment

Calculation of Excess Cancer Risk: Excess cancer risk from the ingestion of natural Uranium from the drinking water has been calculated according to the standard method given by the USEPA [17]. Where 'ECR' is Excess Cancer Risk, 'Ac' is Activity concentration of Uranium (Bq/l) and 'R' is Risk Factor.

12 $ECR = Ac \times R$

The risk factor R (per Bq l⁻¹), linked with ingestion of Uranium from the drinking water may be estimated by the product of the risk coefficient (r) of Uranium (1.19 × 10⁻⁹) for mortality and per capita activity intake I. I for Uranium is calculated as product of life expectancy as 63.7 years, i.e. 23250 days and daily consumption of water as 4.05 l day⁻¹ [18]. $I = 4.05 \text{ l day}^{-1} \times 23250 \text{ days}$

13 Risk Factor (R) = $r \times I$ h) Chemical Risk Assessment

The chemical toxicity risk for Uranium is defined in terms of Lifetime Average Daily Dose (LADD) of the uranium through drinking water intake. LADD is defined as the quantity of the substance ingested per kg of body weight per day and is given by the following equation [19,20].

14 $LADD = C \times IR \times ED \times EF \div AT \times BW \times 365$

Where 'C' is the concentration of the uranium (µg/l), IR is the water consumption rate (4.05 l day⁻¹), ED is the lifetime exposure duration (63.7 years), EF is the exposure frequency (365 days y⁻¹), BW is average body weight of the receptor (70 kg), and AT is the Averaging time i.e. life expectancy (63.7 years).

15 i) Calculation of Hazard Quotient

Hazard quotient (HQ) is the measure of the extent of harm produced due to the ingestion of uranium from the drinking water.

16 $HQ = LADD \div RfD$

Where, LADD is Lifetime Average Daily Dose; RfD is the reference dose = 4.53 µg kg⁻¹ day⁻¹.

17 Results and Discussion

Groundwater samples were collected from villages falling under Mohali and Fatehgarh Tehsils of both these districts of Punjab (India) and analysed for Uranium content using calibrated LED Fluorimeter (Quantalase Make). Uranium content varies from 0.63 ppb (RO filtered water) to 24.20 ppb (Motor Driven Pump) in Mohali district. In Fatehgarh district, the U content varies from 2.14 ppb (RO System in Reona) to 57.82 ppb for a deep bore Tubewell in Banda Bahadur Engg. College Campus. In Badali Mai Ki village, U content in water of hand pump is 17.22 ppb while it is below detection limit (BDL) in RO filtered water being supplied to the village. It clearly proves that RO System is highly efficacious for getting rid of Uranium from groundwater in Punjab. The safe limit of uranium in groundwater is fixed to be 60 ppb by AERB [21] in India, while other agencies fix it in much lower limits of 30 ppb (EPA, USA) [17]; 15 ppb (WHO) [1]; 9 ppb (UNSCEAR) [22] and 1.9 ppb (ICRP) [23]. If the observed data of uranium content of water (Table 1) is compared with the guideline of AERB, none of the samples record higher than 60 ppb, hence qualify the safe limit certification of AERB, Government of India.

18 a) Radiological risk

In the present investigation, uranium content of the ground water samples of the Mohali and Fatehgarh districts of North Punjab has been measured and further analysis has been carried out for the excess cancer risk assessment.

The radiological risk has been calculated due to ingestion of natural uranium in the drinking water, assuming the consumption rate of 4.05 L/day and lifetime expectancy of 63.7 years for both males and females. The excess cancer risk has been observed to be in the range of 0.02 × 10⁻⁴ - 1.64 × 10⁻⁴. The value of the excess cancer risk in the surveyed districts is lower than the maximum acceptable level of 1.67 × 10⁻⁴ according to AERB, DAE guidelines. If we assume lifetime water consumption rate of 4.05 L/day with the present uranium content of water, the mean value of excess cancer risk in the surveyed districts comes out to be 0.48 × 10⁻⁴, which works out to be approximately 1 per 20,000 people.

19 b) Chemical toxicity risk

Uranium is a radioactive heavy metal, so it has health impacts due to its both radioactive and chemical nature. If we take into account chemical toxicity of the uranium, the kidneys are the most important target organ. The chemical toxicity of the uranium dominates over its radiological toxicity on the kidney in general at lower exposure levels [24]. The chemical toxicity has been estimated from the value of lifetime average daily dose (LADD) and Hazard quotient. Hazard quotient has been estimated by comparing the value of the calculated LADD with the reference dose level of $4.53 \text{ } \mu\text{g/kg/day}$. The reference level has been calculated for the maximum contamination level of the uranium in water of $60 \text{ } \mu\text{g/L}$. The variations in the values of the LADD and Hazard quotient are observed from $0.04 \text{ } \mu\text{g/kg/day}$ - $3.35 \text{ } \mu\text{g/kg/day}$ and from 0.01 - 0.74, respectively.

20 Conclusions

The concentration of the uranium in ground water samples collected from the hand pumps or other ground water sources of several villages of Mohali and Fatehgarh districts is found to be within the safe limit of 60 ppb recommended by AERB, India.

The cancer risk due to presence of U in groundwater is almost negligible.

Our investigations establish that uranium content in North Punjab districts is much lower than South Punjab [13,15].



Figure 1:

14
Volume XVI Issue IV Version I
(B)
Global Journal of Human Social Science

[Note: © 2016 Global Journals Inc. (US) s -Year 2016]

Figure 2:

? It will be of interest to study nature of aquifers in North and South Punjab based on geological, morphological and hydrogeological investigations.

Figure 3: ?

¹Natural Uranium Content in Ground Waters of Mohaliand Fatehgarh Districts of North Punjab (India)for the Assessment of Excess Cancer Risk

²© 2016 Global Journals Inc. (US) Natural Uranium Content in Ground Waters of Mohaliand Fatehgarh Districts of North Punjab (India) for the Assessment of Excess Cancer Risk

1

S.No	Location	Water Source	Uranium Concentration (ppb)	Uranium Concentration (Bq l ⁻¹)	Excess Cancer risk *	LADD (?g kg ⁻¹ day ⁻¹)	Hazard Quotient	
1	District Mohali CGC Jhanjheri	Tubewell (T.W.)	10.29	0.26	0.29	0.60	0.13	
2	Jhanjheri	Hand Pump (H.P.)	14.39	0.36	0.41	0.83	0.18	
3	Landran Gurudwara	T.W./M.P.	24.20	0.61	0.69	1.40	0.31	
4	Kargil Park, Sector 71, Mohali	T.W.	12.40	0.31	0.35	0.72	0.16	
5	Majat	H.P.	14.82	0.37	0.42	0.86	0.19	
6	Bharatpur	T.W.	4.92	0.12	0.14	0.28	0.06	17
7 8	Chudiala Chudiala	H.P. H.P.	3.74 7.06	0.09 0.18	0.11	0.22	0.05	Volume
9	Sudan Pattran	M.P. H.P.	10.36	0.26 0.09	0.20	0.41	0.09	XVI
10	Maujpur Mohali	Canal	3.63	0.08 0.02	0.29	0.60	0.13	Is-
11	Water Supply HS	Water	3.26 0.63	1.39 1.46	0.10	0.21	0.05	sue
12	Virk House District	RO T.W.	55.12		0.09	0.19	0.04	IV
1 2	Fatehgarh SGGS	Borewell	57.82		0.02	0.04	0.01	Ver-
	WU Fategarh BBEC	(B.W.)			1.56	3.19	0.70	sion
	Fatehgarh				1.64	3.35	0.74	I
3 4	Atewali Gurudwara	H.P. T.W.	30.57	0.77 0.61	0.87	1.77	0.39	(
	Kotla Bijwara		24.00		0.68	1.39	0.31	B
								)
5	Raipur Gujran	T.W.	25.39	0.64	0.72	1.47	0.32	
6	Badali Ala Singh	Motor Driven Pump (M.P.)	24.62	0.62	0.70	1.42	0.31	
7	Akal Akademi Chuni	T.W.	17.04	0.43	0.48	0.99	0.22	
8	Biromajri	H.P.	2.81	0.07	0.08	0.16	0.04	
9	Bhagrana	H.P.	6.98	0.18	0.20	0.40	0.09	
10	Badali Mai Ki	H.P.	17.22	0.44	0.49	1.00	0.22	
11	Badali Mai Ki	RO	BDL	BDL	BDL	BDL	BDL	
12	Slaimpur	HP on Canal	20.29	0.51	0.57	1.17	0.26	
13	Pola 1	H.P.	18.99	0.48	0.54	1.10	0.24	
14	Pola 2	H.P.	15.3	0.39	0.43	0.89	0.20	
15	Rajindergarh	H.P.	26.24	0.66	0.74	1.52	0.34	
16	Sadugarh	H.P.	6.18	0.16	0.18	0.36	0.08	
17	Hansali	H.P.	22.18	0.56	0.63	1.28	0.28	
18	Dageri	H.P.	24.26	0.61	0.69	1.40	0.31	
19	Hindupur	H.P.	16.76	0.42	0.47	0.97	0.21	
20	Panjola	H.P.	18.14	0.46	0.51	1.05	0.23	
21	Reona Neevan	RO	2.14	0.05	0.06	0.12	0.03	

Figure 4: Table 1 :

- [Somogyi ()] , G Somogyi . *IAEA* 1990. 1 (310) p. 229. (Technical Reports Series)
- [Hdr ()] , Hdr . 2009. Mumbai, India. National Resource Centre for Urban Poverty and All India Institute of Local Self Government (Human development report)
- [Cantaluppi and Degetto ()] ‘Civilian and military uses of depleted uranium: Environment and health problem’. C Cantaluppi , S Degetto . *Ann Chim* 2000. 90 p. .
- [Aerb ()] *Drinking water specifications in India*, Aerb . 2004. Department of Atomic Energy, Govt. of India
- [Guidelines for drinking-water quality WHO ()] ‘Guidelines for drinking-water quality’. *WHO* 2011. World Health Organization. (4) . (th ed.)
- [Lee et al. ()] ‘Human risk assessment of As, Cd, Cu and Zn in the abandoned metal mine site’. J S Lee , H T Chon , K W Kim . *Environ Geochem and Health* 2005. 27 p. .
- [ICRP, International Commission on Radiological Protection ()] *ICRP, International Commission on Radiological Protection*, (Oxford) 1993. Pergamon Press. 23. (ICRP Publication)
- [Life in the 21 st century: A vision for all WHO ()] ‘Life in the 21 st century: A vision for all’. *WHO* 1998. World Health Organization.
- [Bajwa et al. ()] ‘Measurements of natural radioactivity in some water and soil samples of Punjab’. B S Bajwa , Sharma Navjeet , V Walia , H S Virk . *India. Indoor & Built Environ* 2003. 12 p. .
- [S.B.S. ()] ‘Nagar) DISTRICT, PUNJAB. Ministry of Water Resources, Government of India’. *Central Ground Water Board* S.B.S. (ed.) 2012. (Ground water information booklet)
- [Cothorn and Lappenbusch ()] ‘Occurrence of uranium in drinking water’. C R Cothorn , W L Lappenbusch . *US Health Physics* 1983. 45 p. .
- [Bleise et al. ()] ‘Properties, use and health effects of depleted Uranium (DU): a general overview’. A Bleise , P R Danesi , W Burkart . *J. Environ Radioact* 2003. 64 p. .
- [Tripathi et al. ()] ‘Study of uranium isotopic composition in groundwater and deviation from secular equilibrium condition’. R M Tripathi , S K Sahoo , S Mohapatra , P Lenka , J S Dubey , V D Puranik . *J Radioanal Nucl Chem* 2013. 295 p. .
- [Tanner (ed.) ()] *The National Radiation Environment III, National technical Information Services*, A B Tanner . Gesell T.F., Lowder W.M. (ed.) 1980. 1980. Springfield. 1 p. . (Radon migration in the ground, a supplementary review)
- [United Nations Scientific Committee on the Effects of Atomic Radiation) (1982) Ionizing Radiation: Sources and Biological Effects *United Nations Scientific Committee on the Effects of Atomic Radiation) (1982) Ionizing Radiation: Sources and Biological Effects*, New York, NY, USA. UNSCEAR
- [Singh et al. ()] ‘Uranium analysis of geological samples, water and plants from Kulu Area’. S Singh , R Malhotra , J Kumar , B Singh , L Singh . *Radiat Meas* 2001. 34 p. .
- [Bajwa et al. ()] ‘Uranium and other heavy toxic elements distribution in the drinking water samples of SW-Punjab, India’. B S Bajwa , S Kumar , S Singh , S K Sahoo , R M Tripathi . 10.1016/j.jrras.2015.01.002. *J Radiat Res and ApplSci* 2015.
- [Virk ()] ‘Uranium and radon surveys in Western Himalaya’. H Virk . *Curr Sci* 1997. 73 (6) p. .
- [Kumar et al. ()] ‘Uranium content measurement in drinking water samples using track etch technique’. M Kumar , A Kumar , S Singh , R K Mahajan , Tps Walia . *RadiatMeas* 2003. 36 p. .
- [Uranium in drinking water. Document for Public Comment Prepared by Federal Provincial Subcommittee on Drinking Water Health Canada] ‘Uranium in drinking water. Document for Public Comment Prepared by Federal Provincial Subcommittee on Drinking Water’. *Health Canada* 1999.
- [Mehra et al. ()] ‘Uranium studies in water samples belong to Malwa region in Punjab by track etching technique’. R Mehra , S Singh , K Singh . *Radiat Meas* 2007. 42 (3) p. .
- [Atsdr ()] *US Department of Health and Human Services, Agency for Toxic Substances and Disease Registry*, Atsdr . 1990. Atlanta, Georgia. (Toxicological profile for Radium)
- [Atsdr ()] *US Department of Health and Human Services, Agency for Toxic Substances and Disease Registry*, Atsdr . 1999. Atlanta, Georgia. (Toxicological profile for uranium)
- [USEPA (2000) National primary drinking water regulations, radionuclides. Final Rule] *USEPA (2000) National primary drinking water regulations, radionuclides. Final Rule*, Washington, DC. United States Environmental Protection Agency